



millersoils.co.uk

PRODUCT DATA SHEET  
**INDUSTRIAL**



PRODUCT NAME/VISCOSITIES:  
MILLUBE T RANGE

DESCRIPTION:

The Millube T Range is a premium quality solvent refined mineral oil, with the inclusion of a tacky adhesive additive.

APPLICATION:

Use as received where a non additive adhesive mineral oil is required. Highly suitable for horizontal and vertical surfaces where anti drip lubrication is required or oil type automatic lubrication systems.

USER BENEFITS:

- Cost effective, thermally stable product.
- Anti drip adhesive quality gives continuous lubrication.
- Economical in use.
- Clean work environment.

TYPICAL CHARACTERISTICS:

Millube T	150T	220T	320T
Specific Gravity @ 15°C	0.889	0.885	0.900
Kinematic Viscosity @ 100°C	15.1cSt	20cSt	23Cst
Kinematic Viscosity @ 40°C	152cSt	220cSt	310Cst
Viscosity Index	99	96	92
Pour Point (°C)	-9	-9	-9
Flash Point (°C)	200	200	200
Health & Safety/Product Code	5867	5870	5871

HEALTH AND SAFETY:

Health and Safety Data Sheet numbers above relate to the products listed. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

